


Hydraulic Quick Couplings

General Purpose Couplings 60 Series

Couplers

Female Thread




Body Size (in.)	Part No. Brass	Wt. (LB.) P/Piece	Part No. Steel	Wt. (LB.) P/Piece	Part No. Type 303 Stainless	Wt. (LB.) P/Piece	Part No. Type 316 Stainless	Wt. (LB.) P/Piece	Thread Size NPTF	Thread Size ORB	Dimensions (in.)		
											Overall Length	Wrench Flats	Largest Diameter
											A	B	C
1 1/2	BH12-60L	4.58	H12-62L	4.70	SH12-62L	4.68	SSH12-62LY	4.68	1 1/4-11 1/2	–	4.86	2.38 [‡]	3.00
1 1/2	BH12-60N	4.58	H12-62N	4.70	SH12-62N	4.68	SSH12-62NY	4.68	1 1/2-11 1/2	–	4.86	2.38 [‡]	3.00
1 1/2	–	4.61	H12-62-T20	4.72	SH12-62-T20	4.71	SSH12-62Y-T20	4.71	–	1 5/8-12	4.86	2.38 [‡]	3.00
1 1/2	–	4.61	H12-62-T24	4.72	SH12-62-T24	4.71	SSH12-62Y-T24	4.71	–	1 7/8-12	4.86	2.38 [‡]	3.00
2 1/2	BH2016-60	11.06	H2016-62	10.58	SH2016-62	–	SSH2016-62Y	–	2-11 1/2	–	5.57	3.75	4.10
2 1/2	BH2020-60	11.42	H2020-62	10.91	SH2020-62	–	SSH2020-62Y	–	2 1/2-8	–	6.04	3.75	4.10
2 1/2	BH2024-60	–	H2024-62	–	SH2024-62	–	SSH2024-62Y	–	3-8	–	6.96	4.00	4.35

‡Wrench Flat on 303 Stainless is 2.50 in.

Nipples

Female Thread



Body Size (in.)	Part No. Brass	Wt. (LB.) P/Piece	Part No. Steel	Wt. (LB.) P/Piece	Part No. Type 303 Stainless	Wt. (LB.) P/Piece	Part No. Type 316 Stainless	Wt. (LB.) P/Piece	Thread Size NPTF	Thread Size ORB	Overall Length	Dimensions (in.)			
												Exposed Length*	Wrench Flats	Largest Diameter	
												D	E	F	G
1 1/2	BH12-61L	2.96	H12-63L	3.10	SH12-63L	3.06	SSH12-63LY	–	1 1/4-11 1/2	–	4.76	2.69	2.38 [‡]	2.75 [†]	
1 1/2	BH12-61N	2.96	H12-63N	3.10	SH12-63N	3.06	SSH12-63NY	–	1 1/2-11 1/2	–	4.76	2.69	2.38 [‡]	2.75 [†]	
1 1/2	–	–	H12-63-T20	3.15	SH12-63-T20	3.14	SSH12-63Y-T20	–	–	1 5/8-12	4.76	2.69	2.38 [‡]	2.75 [†]	
1 1/2	–	–	H12-63-T24	3.15	SH12-63-T24	3.14	SSH12-63Y-T24	–	–	1 7/8-12	4.76	2.69	2.38 [‡]	2.75 [†]	
2 1/2	BH2016-61	7.78	H2016-63	7.90	SH2016-63	7.92	SSH2016-63Y	–	2-11 1/2	–	5.48	2.90	3.75	4.10	
2 1/2	BH2020-61	8.12	H2020-63	8.16	SH2020-63	8.16	SSH2020-63Y	–	2 1/2-8	–	5.95	3.37	3.75	4.10	
2 1/2	BH2024-61	–	H2024-63	–	SH2024-63	–	SSH2024-63Y	–	3-8	–	6.87	4.29	4.00	4.35	

* This dimension represents the portion that is exposed when the nipple is inserted into the mating Parker Coupler.

† Largest diameter on Brass is 2.96" across Hex Corners

‡ Hex on 303 Stainless is 2.50 in.

Replacement Parts

60 Series Couplers

Body Size (in.)	O-Rings - Nitrile	Back-Up Rings
1/8	50001-013-0010	H67A-28
1/4	50001-015-0010	H67C-28
3/8	50001-116-0010	4118007
1/2	50001-213-0010	4128002
3/4	50001-218-0010	4148001
1	50001-222-0010	4158001
1-1/2	50001-124-0010 (Valve)	50001-138-0260 (Fitting) 50001-224-0010 (Body 2 req.)
2-1/2	50001-133-0010 (Valve)	50001-234-0260 (Fitting) 50001-333-0010 (Body)

Repair Kits

Couplers

Nipples

Body Size (in.)	Repair Kit Part No.	Used For Part No.	Repair Kit Part No.	Used For Part No.
3/8	H67E-62K BH67E-60K SH67E-62K SSH67E-62KY	H3-62 BH3-60 SH3-62 SSH3-62Y	H67E-63K BH67E-61K SH67E-63K SSH67E-63KY	H3-63 BH3-61 SH3-63 SSH3-63Y
1/2	H67F-62K BH67F-60K SH67F-62K SSH67F-62KY	H4-62 BH4-60 SH4-62 SSH4-62Y	H67F-63K BH67F-61K SH67F-63K SSH67F-63KY	H4-63 BH4-61 SH4-63 SSH4-63Y
3/4	H67G-62K BH67G-60K SH67G-62K SSH67G-62KY	H6-62 BH6-60 SH6-62 SSH6-62Y	H67G-63K BH67G-61K SH67G-63K SSH67G-63KY	H6-63 BH6-61 SH6-63 SSH6-63Y
1	H67J-62K BH67J-60K SH67J-62K SSH67J-62KY	H8-62 BH8-60 SH8-62 SSH8-62Y	H67J-63K BH67J-61K SH67J-63K SSH67J-63KY	H8-63 BH8-61 SH8-63 SSH8-63Y

