

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

1E and 1R Series Compact Utility Tractors - 1023E, 1025R, 1026R

FILTER PAK
(1023E, 1026R) – [LVA21035](#)

(1025R) – [LVA21036](#)

Each kit contains oil filter, air filter, fuel filter, and hydraulic filter, offering a complete solution for your maintenance needs to keep your tractor running at peak performance.

ENGINE

OIL FILTER

[M806418](#)

Replace every 200 hours and annually if less than 200 hours of operation.
(Click here for [capacity](#))

ENGINE

INLINE FUEL FILTER

[AM116304](#)

Replace every 400 hours and annually.
(Click here for [capacity](#))

TRANSMISSION

HYDRAULIC FILTER

[LVA16054](#)

Replace after first 50 hours and every 200 hours.
(Click here for [capacity](#))

ENGINE

FUEL FILTER

[M801101](#)

Replace every 400 hours and annually.
(Click here for [capacity](#))

ENGINE

PRIMARY AIR FILTER

(1023E, 1026R) – [M113621](#)

(1025R) – [M131802](#)

SECONDARY AIR FILTER

(1023E, 1026R) – [M123378](#)

(1025R) – [M131803](#)

Replace every 400 hours and as required.

Check and service every 10 hours/daily, every 200 hours and annually. (Service 1025R, 1026R when restriction indicator is red).

(Click here for [capacity](#))



JOHN DEERE
Genuine Parts and Service

CAPACITIES

1E and 1R Series Compact Utility Tractors - 1023E, 1025R, 1026R

CAPACITIES (Approximate):

Fuel Tank:

..... 21.2 L (5.6 gal)

Cooling System:

Cool-Gard™ II

..... 3.7 L (3.9 qt)

Crankcase with Filter:

Plus-50™

..... 2.7 L (2.9 qt)

Transmission and Hydraulic System:

Hy-Gard™

..... 12.3 L (3.3 gal)

Front Axle:

Hy-Gard™

..... 2.8 L (3.0 qt)

[Return to Filter Overview](#)



JOHN DEERE
Genuine Parts and Service