

---

# *The K2 Series*

*T233HST and T273HST*

*A sleek, compact design with big-time functionality*

**TM**



# K2 Series Specifications

TYM is constantly improving its products and reserves the right to change the specifications herein without notice.

Feature		T233HST	T273HST	
ENGINE	Manufacturer	Mitsubishi	Mitsubishi	
	Model	S3L	S3L2	
	Gross Power, hp (kw)	23 (16.9)	27 (19.8)	
	Rated Speeds, RPM	2,700	2,700	
	Number of Cylinders	3	3	
	Displacement, cu. in. (cc)	68.6 (1125)	80.4 (1318)	
ELECTRICAL	Air Cleaner	Single Dry	Single Dry	
	Alternator	12V, 47A	12V, 47A	
ELECTRICAL	Starter Motor	12V, 1.6Kw	12V, 1.6Kw	
FUEL SYSTEM	System Type	Indirect Fuel Injection	Indirect Fuel Injection	
	Fuel	Diesel	Diesel	
	Fuel Tank Capacity, US gal. (L)	6.6 (25)	6.6 (25)	
DRIVE TRAIN	Transmission	HST	HST	
	Number of Speeds	Infinite / 2 Range	Infinite / 2 Range	
	Max. traveling speed, mph (km/h)	10.0 (16.2)	10.0 (16.2)	
	Brakes	Wet Disc	Wet Disc	
	4WD (MFWD)	Standard	Standard	
	Steering	Hydrostatic Power	Hydrostatic Power	
	Differential Lock	Yes	Yes	
3-POINT HITCH	Category	I	I	
	Hitch lift capacity, lb. (kg) @ 24" behind lift arms	1213 (550)	1213 (550)	
HYDRAULIC SYSTEM	Pump Type	Gear Pump x 2	Gear Pump x 2	
	Implement Pump capacity, gpm (L/min)	5.0 (18.9)	5.0 (18.9)	
	Steering Pump capacity, gpm (L/min)	2.6 (10)	2.6 (10)	
	Maximum Total Flow, gpm (L/min)	7.6 (28.9)	7.6 (28.9)	
	Lift Control Type	Position	Position	
	Auxiliary Hydraulics	1 Set	1 Set	
PTO	Rear, rpm	540	540	
	Mid, rpm	2000	2000	
DIMENSIONS (with standard tires)	Overall Length, in. (mm) with 3P	94.48 (2340)	94.48 (2340)	
	Overall Width, in. (mm)	49.6 (1244)	49.6 (1244)	
	Height to Top of ROPS, in. (mm)	78.74 (2000)	78.74 (2000)	
	Wheelbase, in. (mm)	58.26 (1480)	58.26 (1480)	
	Min. Ground Clearance, in. (mm)	12.6 (320)	12.6 (320)	
	Weight, lb. (kg)	1962 (750)	1962 (750)	
TIRE SIZE	R1	Front	6-12	6-14
	R1	Rear	9.5-20	11.2-20
	R3	Front	23x8.50-12, 4PR	23x8.50-12, 4PR
	R3	Rear	12-16.5, 4PR	12-16.5, 4PR
	R4 (standard)	Front	23x8.50-12, 4PR	23x8.50-12, 4PR
	R4 (standard)	Rear	12-16.5, 6PR	12-16.5, 6PR
SAFETY	ROPS	Standard	Standard	



## TYM America US Headquarters

7301 Allentown Road  
Harrisburg, PA 17112  
Phone: 888.357.5105  
Fax: 717.540.5863

## TYM USA Western

Distribution Center  
1204 SW Lake Road  
Redmond, OR 97756  
Phone: 541.504.0128  
Fax: 541.504.0237

## TYM America Southern Warehouse

300 N. 9th Highway 146 N.  
La Porte, TX 77571  
Phone: 281.470.1725  
Fax: 281.470.2523

[www.tym-america.com](http://www.tym-america.com)

## For 5 Years You Are Now Covered!



Every TYM tractor is designed and manufactured to the highest standard, with uncompromising attention being paid to detail. Prior to leaving the factory, detailed inspection of each unit is carried out prior to shipping, ensuring that the next unit shipped is as good as the last. TYM has the highest level of equipment as standard. As a result of this dedication to quality and reliability that is second to none, TYM, the manufacturer, provides a 5-year warranty\* standard with every tractor.

\*Conditions Apply.

**QUALITY MATTERS!**