

	LS U5020 US Ver	LS U5030 US Ver	LS U5030C US Ver	LS U5030C Asia Ver U60C	LS P7010C US Ver	LS P7010C Asia Ver PLUS70
Engine						
Engine Model	S4QL (Mitsubishi	Mitsubishi S4S	Mitsubishi S4S	Mitsubishi S4S	Iveco F5C Turbo	Iveco F5C Turbo
Engine Gross Power	47	55	55	55	72	72
Rated Speed	2,600	2500	2500	2500	2300	2300
No. of Cylinder	4	4	4	4	4	4
Fuel Type	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
Aspiration	Indirect Injection	Indirect Injection	Indirect Injection	Indirect Injection	Turbo	Turbo
Displacement	152.9	203.3	203.3	152.8	195.3	195.3
Fuel Tank Capacity	15.9	15.9	15.9	15.9	26.4	26.4
Pre-heating System	Glow Plug	Glow Plug	Glow Plug	Glow Plug	Glow Plug	Glow Plug
Alternator	12V - 50 Amp	12V-50 Amps	12V-50 Amps	12V-50 Amps	12V-120 Amps	12V-120 Amps
Transmission Type						
Shuttle	Synchro	Synchro shuttle	Synchro shuttle	Synchro shuttle	Synchro shuttle	Synchro shuttle
Main Gear						
No. of Travel Speed Forward / Reverse	16F/16R	16F / 16R	16F / 16R	16F / 16R	20F / 20 R	20F / 20 R w/creeper
Power Take Off						
PTO Type Trans	Full Independent or Manual	Full Independent or Manual	Full Independent or Manual	Full Independent	Full Independent or Manual	Full Independent
PTO Power	42	48	48	50	63	63
Rear PTO Speeds	540	540	540	540	540/750/1000	540/750/1000
Brakes and Clutch						
Brakes	Wet, Multi Disc	Wet, Multi Disc	Wet, Multi Disc	Wet, Multi Disc	Wet, Multi Disc	Wet, Multi Disc
Clutch	Dry	Dry	Dry	Dry	Dry	Dry
Dimensions w/ AG Tire						
Length w/ 3-point hitch	135.2	135.2"	135.2"	147.9	157.1	157.1
Width	65.7	66.9"	66.9"	66.9"	77.8	77.8

	LS U5020 US Ver	LS U5030 US Ver	LS U5030C US Ver	LS U5030C Asia Ver U60C	LS P7010C US Ver	LS P7010C Asia Ver PLUS70
Height from Top of ROPS	102.3	102.3"				
Height from Top of Cab			95.5	95.5	102.3	102.3
Height from Top of ROPS Folded						
Wheelbase	76	80.6"	80.6"	80.6"	86.6	86.6
Hydraulics						
Total Pump Flow	14.5	14.7	14.7	14.7	19	19
Main Pump Capacity	9.6	9.9	9.9	9.9	12	12
Power Steering Pump Capacity	4.9	4.8	4.8	4.8	7	7
Remote Valves	2	2	2	3	3	3
3-Point Hitch						
Standard Category	CAT 1	CAT 2	CAT 2	CAT 2	CAT 2	CAT 2
Lift Capacity, 24" aft of hitch, lb	4079	4079	4079	3867	6173	6186
Control Type Position	Position	Position	Position	Position	Position and Draft	Position
Weight (AG Tires)	4280	4600	5000	4861	6675	6688
Standard Equipment						
Adjustable Seat with Seat belt	X	X	X	X	X	X
Automatic Lift Arm	X	X	X	X	X	X
Remote Hydraulic Valve	2	2	2	3	3	3
Cabin with Heat and A/C			X	X	X	X
Foldable ROPS	X	X				
Hand & Foot Throttles	X	X	X	X	X	X

	LS U5020 US Ver	LS U5030 US Ver	LS U5030C US Ver	LS U5030C Asia Ver U60C	LS P7010C US Ver	LS P7010C Asia Ver PLUS70
Headlights	X	X	X	X	X	X
Hydrostatic Power Steering	X	X	X	X	X	X
Safety Lights	X	X	X	X	X	X
Rear Differential Lock	X	X	X	X	X	X
Rear Working Light	X	X	X	X	X	X
Single Lever Joy Stick For Loader Operation	X	X	X	X	X	X
Drawbar	X	X	X	X	X	X
Telescopic Lower Link Ends	X	X	X	X	X	X
Telescopic stabilizer	X	X	X	X	X	X
7-pin Rear electrical connector	X	X	X	X	X	X
Turn signals	X	X	X	X	X	X
Wet Disc Brakes	X	X	X	X	X	X
Instrument Panel						
4WD indicator						
Alternator	X	X	X	X	X	X
Battery Charge indicator						
Fuel Gauge	X	X	X	X	X	X
Glow Plug Indicator						
Hydraulic Warning						
Low Coolant Indicator	X	X	X	X	X	X

	LS U5020 US Ver	LS U5030 US Ver	LS U5030C US Ver	LS U5030C Asia Ver U60C	LS P7010C US Ver	LS P7010C Asia Ver PLUS70
Low Fuel Indicator						
Oil Pressure Indicator	X	X	X	X	X	X
Parking Brake Operation Indicator						
PTO Indicator						
Separate Detector						
Shuttle Neutral Indicator						
Tachometer with Hour Meter	X	X	X	X	X	X
Temperature Gauge						
Optional Equipment						
Front suitcase weights	X	X	X	X	X	X
Front PTO						
2nd Remote Hydraulic Valve						
Sunshade						
Mid PTO						
Trailer Electronic Outlet (7 Pin Socket)						
Working Lamp						