

**Solenoid Operated  
Double  
Selector****ITEM 9-1782****\$259.95**

• Brand new PARKER Model MS06-UDNA-12B double selector valve. Allows one double acting control valve to control your choice of 2 different cylinders. These valves can be ganged together giving multiple circuit capability.

**SPECIFICATIONS**

- 12 VDC coil
- GPM 8 max.
- 4 amps
- PSI 3000 max.
- Ports SAE 6
- Size 8 1/2" x 2 1/2" x 2 1/2"
- Shpg. 9 lbs.

**Solenoid Operated  
Double  
Selector  
Valve****ITEM 9-5117****\$149.99**

• Brand new. Dual 12 volt DC solenoid operated double selector/multiplier valve. Allows one double acting control valve to operate your choice of two double acting cylinders or motors. Ideal for use with tractor remotes. When used with "variable flow" or "closed center" systems valve can be used as a selector, or power both solenoids and direct fluid to both circuits at the same time.

**SPECIFICATIONS**

- 3000 PSI
- 15 GPM
- 12 volt DC
- Ports SAE 8
- Size 4 1/2" x 2 1/2" x 6 1/2"
- Shpg. 7 lbs.

**12 VDC Triple  
Selector  
Valve****ITEM 9-6865**  
**\$149.95**

• New, triple selector valve originally built for use on CATERPILLAR skid-steer loaders. Part # 155-5569-GP04. Allows one directional control valve to control three separate circuits. First circuit is prioritized so first solenoid must be powered to turn first circuit off. Second or third solenoids must be powered to select their circuits after first circuit is turned off. Check valve in "A" port in the third circuit. Restrictor fitting (0.045" orifice) installed in the P1 inlet port can easily be removed, restricts flow to all three "A" ports. Wire leads with DEUTSCH DT04-2P weatherpac connectors. First selector has a built-in restriction to restrict flow to the actuator (e.g. for use with a grapple).

**SPECIFICATIONS**

- 12 GPM max
- 3000 PSI max
- 12 VDC
- 1.50 amps per solenoid
- Ports SAE 6
- Size 5 1/2" x 1 3/4" x 5 1/4"
- Shpg. 10 lbs.

**Ordering Information  
& UPS Rates  
on pages 150 - 151**

**Double  
Selector  
Valve****ITEM 900**  
**\$108.95**

• Brand new PARKER. Allows one control valve to operate 2 different double acting cylinders or reversible motors. Also use to operate two different circuits from one valve.

**SPECIFICATIONS**

- 24 GPM
- 2000 PSI
- Size 8 1/2" x 3 1/4" x 8"
- Ports 3/4" NPT
- Chrome plated press. balanced spool
- Shpg. 12 lbs.

**Double  
Selector  
Valves**

• Brand new PRINCE. Allows one control valve to operate two different double acting cylinders or reversible motors. Also use to select between two different circuits from one hydraulic source. 2500 PSI. Shpg. 14 lbs.

**ITEM 9-4128**

• 20 GPM, ports 1/2" NPT.

**ITEM 9-6131**

• 30 GPM, ports 3/4" NPT.

**ITEM 9-6132**

• 40 GPM, ports 1" NPT.

**Float  
Position  
Valve**

• New PARKER Model HM-Series. For snow plows, loaders, winches and similar equipment. Use with standard 4 way, 3 position valves to provide a float or free wheeling position. 10 GPM, max. 2000 PSI, chrome plated pressure balanced spool. Size 6" x 3" x 2 1/4". Shpg. 5 lbs.

**ITEM 9-1064**

• Brand new, ports 1/2" NPT.

**ITEM 9-4352**

• New, ports SAE 8.

**Two-Way  
Selector  
Valve****ITEM 9-6601**  
**\$49.99**

• New GRESEN Model S16. Direct pump flow to two independent hydraulic circuits. Clevis end on spool for remote cable operation.

**SPECIFICATIONS**

- Pressure balanced spool
- PSI 3000 max.
- Ports SAE 16
- GPM 40
- Size 7 1/4" x 4 1/2" x 3 1/2"
- Shpg. 9 1/2 lbs.

**Two-Way  
Selector  
Valves**

• Brand new PARKER. Operate two independent hydraulic circuits from one pump (operate a blade and bucket on the same machine with only a single control valve). With several selector valves many separate systems can be installed and operated. Pressure balanced spool. Max. 2000 PSI. Size 5 3/4" x 3 1/4" x 2 1/2".

**ITEM 9-004**

• 1/2" NPT, 15 GPM. Shpg. 5 lbs.

**ITEM 9-004-A**

• 3/4" NPT, 24 GPM. Shpg. 7 lbs.

**ITEM 9-004-B**

• 3/8" NPT, 20 GPM. Shpg. 4 lbs.

**ITEM 9-2901**

• 1" NPT, 40 GPM. Size 7 1/4" x 4 1/2" x 3 1/2". Shpg. 9 1/2 lbs.

**ITEM 9-2277**

• New. SAE 12, 24 GPM. Shpg. 9 lbs.

**Selector  
Valve****ITEM 9-6133****\$55.95**

• Brand new PRINCE. Two position two-way selector valve. Directs pump flow to select between two circuits. Also use to select between two different single acting hydraulic cylinders from one valve.

**SPECIFICATIONS**

- Model SS1A1D
- GPM 10
- PSI 2500
- Two position
- Ports 3/8" NPT
- Size 5 1/8" x 3 1/4" x 2 1/4"
- Shpg. 6 lbs.

**ITEM 9-6134**

• Same as ITEM 9-6133 above except Model SS2A1D. 15 GPM, ports 1/2" NPT.

**Parker  
Selector  
Valve****ITEM 9-2718**  
**\$42.50**

• New, Model VSIS6. Use to divert pump flow between two different circuits. Rated 50 GPM, 2000 PSI. Three ports SAE 12. 5/16" pin hole on spool end. Shpg. 6 lbs.

**Relief  
Valve****ITEM 9-6882****\$18.95**

• New GRESEN J50-NJ-HP ball and spring relief valve. Two port design. Non-adjustable pressure setting.

**SPECIFICATIONS**

- Flow 20 GPM
- Ports 1/2" NPT
- Pressure setting 1800 PSI
- Size 3" x 2 1/4" x 3 1/4"
- Shpg 3 lbs.