

*Worksaver.*

*Designed.  
Engineered.  
Remarkable  
Value.*



# Compact Tractor Grapple Rake Attachment

Designed for compact tractors up to 40 horsepower that are equipped with a front loader. This 60-inch wide grapple allows the acreage owner unsurpassed versatility in clearing brush, piling limbs or orchard maintenance.



# Worksaver®

## Compact Tractor Grapple Rake Attachment

- Ideal for loading limbs, orchard prunings, raking and piling brush and other hard to handle materials.
- Unique upper grapple design provides clamping force to hold material securely.
- Design to be used with compact tractors of 40 HP or less.
- Design allows brush and other materials to be picked up while leaving the dirt.
- Great for picking up / piling cut limbs and treetops when clearing land.
- Size compatible with the lift capacity of most small loader tractors.
- Good forward visibility for easy control in close quarters for increased productivity.
- Simple efficient design with few moving parts for long life.
- Upper grapple is 34-inches wide for excellent material retention, controlled by single 2 x 8 cylinder.
- Pivot points have lubrication capabilities.
- Tractor front loader model allow use of standard pin-on bracket or select interfacing quick attach brackets for John Deere, AGCO, CNH, Kubota and other brands.
- Model FLGR-4062S is designed for compact tractor front loaders that are equipped with the “Universal” skid steer quick attach system. **It is not designed to be fit to a skid steer loader.**

### Designed for Tractors up to 40 HP Only

Overall width (in/mm) .....	60/ ( 1524 mm)
Overall depth (in/mm) .....	23/ ( 584.2 mm)
Overall height (closed) (in/mm) .....	38.77 / (984.75 mm)
Tine spacing (in/mm) .....	15 / (381 mm)
Grapple opening (in/mm) .....	27 / (685.8 mm)
Number of lower tines .....	5
Width of upper grapple (in/mm).....	34 / (836.6)
Reinforcing tubes between lower tines .....	Yes
Number of cylinders .....	1
Cylinder Specifications	
Bore (in/mm) .....	2 / (50.8 mm)
Stroke (in/mm) .....	8 / (203.2 mm)
Rod diameter (in/mm) .....	1.125 / (28.57 mm)
Pressure (psi/bar) .....	2500 / (172.4)

#### Model FLGR-4062

Mounting Tractor Loader .....	Mgt Brt available *
Weight Skid Steer (lb./kg) .....	359 / (180.98 kg)
Product Computer Number Tractor Loader .....	811460

#### Model FLGR-4062S

For Loaders with Skid Steer Mount .....	“Universal” Skid Steer+
Weight Skid Steer (lb./kg) .....	364/ (180.98 kg)
Product Computer Number Skid Steer .....	811480

*Be sure tractor is properly counterbalanced.*

\*Optional Quick Attach brackets available

**+ Not for use on skid steer loaders**



**READ AND UNDERSTAND OPERATOR'S MANUAL BEFORE OPERATION.**

Worksaver Inc. has a corporate policy of continuous product improvement and development; therefore, specifications are subject to change without any advance notice. Worksaver Inc. is not responsible for differences between specifications or illustrations contained in this publication and the actual equipment.

*Worksaver.*

*Designed.  
Engineered.  
Remarkable  
Value.*



**Worksaver, Inc.**

P.O. Box 100, Litchfield, IL 62056-0100  
Phone: 217-324-5973 • Fax: 217-324-3356  
E-mail: [sales@worksaver.com](mailto:sales@worksaver.com)  
Web: [www.worksaver.com](http://www.worksaver.com)

**Information Provided By:**

