



[View Items in Cart](#)

1-800-488-3407

- PNEUMATICS
- ELECTRICAL
- ENGINES/AUTOMOTIVE
- HYDRAULICS**
- POWER TRANSMISSION
- WATER PUMPS
- WHEELS/CASTERS
- WINCHES
- MISC.



[Home](#) > [Hydraulic](#) > [Sort](#) > Item

BROWSE

- [Free Catalog](#)
- [Community Forum](#)
- [Tech Help](#)
- [Links](#)
- [Product Index](#)

HYDRAULIC

CYLINDERS

- Double Acting
 - Up to 1.9" Bore**
 - 2-2.9" Bore**
 - 3-3.9" Bore**
 - 4-4.9" Bore**
 - 5-5.9" Bore**
 - 6-6.9" Bore**
 - 7" and larger Bore**

- Single Acting
- Power Steering
- Telescoping
- Trunnion

MOTORS

- Low Speed High Torque (under 1000 RPM)
 - Up to 4.9 cu. in. Displ.**
 - 5-9.9 cu. in. Displ.**
 - 10-14.9 cu. in. Displ.**
 - 15-19.9 cu. in. Displ.**
 - 20 or more cu. in. Displ.**
- High Speed Low Torque (over 1000 rpm)
- Wheel Motors / Wheel Hubs

POWERPACKS

- AC Powerpacks
- DC Powerpacks
- Shaft Drive Powerpacks
- Powerpack Replacement Motors
- Replacement Reservoirs

POWER STEERING

- Power Steering Pumps
- Power Steering Valves
- Steering Wheels and Columns
- Power Steering Cylinders

PUMPS

- 2 Stage (log splitter) Pumps
- Hydrostatic Pumps
- Pressure Compensated
- Single Pumps **CW CCW REV.**
- Double Pumps **CW CCW**
- Triple Pumps **CW**
- Clutch Pumps
- PTO Pumps
- Hand/Air Powered Pumps

CONTROL VALVES

- Double Acting
- Single Acting
- Combination
- AC Solenoid Valves
- DC Solenoid Valves
- Stack Valves
- Pilot Operated
- Valve Accessories

ACCESSORY VALVES

- Check/Lock Valves



Enlarge

Item# 9-6137

Our Price \$109.95

12 VDC 10 GPM OC MOTOR SPOOL SOLENOID VALVE

7 In [Stock](#)

[About Our Products](#)

This Item is on [pg. 22](#) of our [2009 CATALOG](#)
[Click here to view PDF page](#)

QTY [Add to Cart](#)

Calculate Domestic Shipping & Handling Estimate

- Item Specs**
- Wiring**

12 VDC HYDRAULIC SOLENOID VALVE

Brand new, EATON-VICKERS DG4V-3 series, double-solenoid control valve. Spring centering spool. Manual override on solenoids. Subplate mounting requires D03 subplate (sold separately) for port connections. Use with two Hirschmann connectors (sold separately) for wiring.

SPECIFICATIONS

- Open center spool
- All ports open to tank in neutral
- Model DG4V-3-0C-MUG7-60
- Voltage 12 VDC
- Amperage 3.5 Amps
- Flow 10.5 GPM max
- Pressure 3,000 PSI max
- Use with D03 subplate
- Size 8-11/16" x 1-7/8" x 2-1/8"
- Shpg. 6 lbs.

RELATED ITEMS



[HIRSCHMANN CONNECTOR FOR DG4V3 SOLENOID VALVE](#)



[1 STATION D03 SUBPLATE OPEN CENTER](#)



[2 STATION D03 SERIES OC SUBPLATE](#)



[3 STATION D03 SERIES OC SUBPLATE](#)

Divider Valves
 Flow Control
 Relief/Cushion Valves
 Selector Valves
 Ball Valves
 Other Valves

HYDRAULIC ADAPTERS

NPT to NPT
 SAE O-ring to NPT
 JIC to NPT
 SAE O-ring to SAE O-ring
 JIC to SAE O-ring
 JIC to JIC
 British Pipe to NPT
 Face Seal

HYDRAULIC FITTINGS/COUPLERS/SUBPLATES

Plugs/Caps - NPT, SAE O-ring, JIC
 Hose Barb - NPT, SAE O-ring
 Flanged Port
 Reusable Couplings
 Quick Couplers
 Live Swivels
 Subplates
 Weld-in Tank Flanges

HYDRAULIC HOSE

Hose Assemblies

With NPT Male Ends
1/4" 3/8" 1/2" 3/4" 1"
 With JIC Female Ends
1/4" 3/8" 1/2" 3/4" 1"
 With Misc Ends
 Bulk Hose

HOISTS

Pickup/Truck Hoists
 Trailer/Wagon Hoists

GAUGES

Dry
 Liquid Filled

TANKS, FILTERS, OIL COOLERS

Filters, Breathers
 Tanks
 Oil Coolers

ACCESSORIES

Cylinder Pins & Mounts
 Manuals, Books
 Repair Kits
 Pump/Motor Mounts
 Miscellaneous



We Ship World Wide
world@surpluscenter.com



For information about this website send email to: webguy@surpluscenter.com