

 <b>CK20S</b>	 <b>CK20S HST</b>	 <b>CS2410</b>
<b>Engine Gross Power</b>	22 hp (16.4 kW)	22 hp (16.4 kW)	24.5 hp (18.3 kW)
<b>No of Cylinders</b>	3	3	3
<b>Transmission Type</b>	Manual	Hydrostatic	Hydrostatic
<b>Shuttle</b>	N/A	N/A	N/A
<b>No. of Travel Speed Forward/Reverse</b>	6F/2R	INF. 2 Range	INF 2 Range
<b>PTO Type</b>	Transmission	Live	Independent
<b>PTO Power</b>	17.1 hp (12.8 kW)	16.2 hp (12.1 kW)	19.4 hp (14.4 kW)
<b>Total Pump Flow</b>	7.66 gpm (29 Lpm)	7.66 gpm (29 Lpm)	6.5 gpm (24.6 Lpm)
<b>Main Pump Capacity</b>	N/A	N/A	N/A
<b>Lift Capacity</b>	1,305 lbs. (592 kg)	1,305 lbs. (592 kg)	700 lbs. (318 kg)
<b>Length With Hitch</b>	Cat. I (N/A)	Cat. 1 (N/A)	Cat. 1
<b>Width</b>	44.1 in. (1,121 mm)	44.1 in. (1,121 mm)	46.5 in. (1,181 mm)
<b>Height From Top of ROPS</b>	86.0 in. (2,185 mm)	86.0 in. (2,185 mm)	88 in. (2,235 mm)
<b>Height From Top of Cab</b>	N/A	N/A	N/A
<b>Wheelbase</b>	57.9 in. (1,470 mm)	57.9 in. (1,470 mm)	55.1 in. (1,400 mm)
<b>Ground Clearance</b>	12.2 in. (310 mm)	12.2 in. (310 mm)	6.4 in. (162 mm)
<b>Weight With Ag Tires and ROPS</b>	2,125 lbs. (964 kg)	2,138 lbs (907 kg)	1,485 lbs. (675)
<b>Weight With Ag Tires and Cab</b>	N/A	N/A	N/A